



# Oh! Dynamic White



Floor Lamp | 1 x powerLED 12 W DC 220 mA | CRI 80  
Dynamic White  
**16228**



Ø 380

Technical data	
Type	Floor Lamp
Installation position	Floor - Land
Installation environment	Outdoor
Light Source	LED
Optics	General Lighting
Light emission direction	downward and upward
Power	12 W
Current intensity	220mA
CCT / Tone	Dynamic White
Colour rendering index	80 Ra
C.C. / C.V.	CC
Safety class	3
IP	IP65
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	No
Dimmable article	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	5 m
Resin potting	No
Type of light emission	Double emission
Net weight	2.6 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing	
Material	PC
Colour	white

Finishing diffuser	
Material	PE
Colour	neutral

## Electronics



99741  
Multi Channel 24~48V DC



84647  
Switching Driver 88~264V AC / 125~373V DC 75 W

Floor Lamp | 1 x powerLED 12 W DC 220 mA | CRI 80 | Dynamic White  
**16228**

Double emission floor lamp for outdoor application. The dynamic white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 1800K-5000 K and a CRI 80.

The device body is made of PC and features a white finish; the diffuser is made of pe. The ingress protection degree is IP65; the total weight is of 2.6 kg. The power supply driver is not provided and is to be ordered separately.










The total absorbed power is 12 W. The power supply cable is included and features a 5 m lenght.

The device features protection class III and can be floor or land-mounted with an outer casing, code 14930(for concrete or masonry).

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L70 B20 C0 50000h (at Tj 115 Ta 25 )	

Oh! Dynamic White | Floor Lamp | Accessories  
16228

		Outer casing - outer casing for installation on ground or on concrete	<div>Code</div> <div>14930</div>
		Pegs installation position: land,Cover material: pc	<div>Code</div> <div>14931</div>
		anti-theft - anti-theft ground fixing bracket	<div>Code</div> <div>14080</div>
		Connector	<div>Code</div> <div>14992</div>
		Remote RF - Dynamic white controller	<div>Code</div> <div>99701</div>